

IN THE CLAIMS

1-14. (Cancelled)

15. (Previously Presented) A tubing device, said tubing device comprising:

a support member having at least one substantially planar surface;

a channel formed in the at least one substantially planar surface, the channel having at least a semi-circular cross-section and lying in substantially a single plane; and

a means for holding a piece of tubing in the support member, the means comprising the channel having at least a semi-circular cross-section, with adhesive being used if the cross-section is not of a greater than semi-circular cross-section.

16. (Cancelled)

17-19. (Cancelled)

20. (Previously Presented) A tubing device, said tubing device comprising:

a tube support comprising a curvilinear channel disposed therein for receiving a piece of tubing; and

means for holding a piece of tubing in said channel wherein said tube support comprises:

a first portion and a second portion; and

said first and second portions being connected by a hinge.

21. (Previously Presented) The tubing device according to claim 20, wherein each of said first portion and said second portion of said tubing device comprises a channel.

22. (Previously Presented) The tubing device according to claim 21, wherein said channel in said first portion and said channel in said second portion are configured to align with each other to hold a piece of tubing between them.

23. (Previously Presented) The tubing device according to claim 22, wherein said channel in said first portion and said channel in said second portion are configured to form a cylindrical channel when aligned.
24. (Previously Presented) The tubing device according to claim 23, wherein said channel in said first portion and said channel in said second portion each has a semi-circular cross section.
25. (Previously Presented) The tubing device according to claim 23, wherein said channel in said first portion has a greater than semi-circular cross section, and said channel in said second section has a less than semi-circular cross-section.
26. (Withdrawn) The tubing device according to claim 15, wherein said curvilinear channel is a first curvilinear channel, and said support member comprises a second curvilinear channel, said second curvilinear channel being disposed adjacent to said first curvilinear channel and within said support member.
27. (Withdrawn) The tubing device according to claim 26, wherein said second curvilinear channel has a diameter less than the cross section of said first curvilinear channel.
28. (Withdrawn) The tubing device according to claim 27, comprising first and second pieces of flexible tubing, said first piece of flexible tubing being disposed in said first curvilinear channel, and said second piece of curvilinear tubing being disposed in said second curvilinear channel.
29. (Withdrawn) The tubing device according to claim 27, wherein the outer periphery of said first channel overlaps the outer periphery of said second channel.
30. (Withdrawn) The tubing device according to claim 27, wherein said support device comprises a barrier between said first and second channels, said barrier comprising a slot to allow communication between said first and second channels.

31. (Currently Amended) The tubing device according to claim 15, wherein said support member comprises:

an opposing, substantially planar, surface opposite the at least one substantially planar surface; and

an additional curvilinear channel, the additional curvilinear channel being formed in the opposing, substantially planar surface.

32. (Previously Presented) The tubing device according to claim 15, wherein said support member comprises an aperture for hanging said tubing device.

33. (Previously Presented) The tubing device according to claim 15, wherein said support device comprises opposing faces and a circumferential edge, and said curvilinear channel comprises a trough disposed along at least a portion of said circumferential edge.

34. (Previously Presented) The tubing device according to claim 15, wherein said support device comprises apertures to reduce the weight of said support device.

35. (Previously Presented) A tubing device for transporting a biological fluid, said tubing device comprising:

a tube support comprising a planar surface having a curvilinear channel disposed therein for receiving a piece of tubing; and

structure to hold a piece of flexible intravenous tubing stationary in said channel.

36. (Previously Presented) The tubing device according to claim 25, further comprising a piece of flexible tubing disposed in said channel.

37. (Previously Presented) A method for transporting a fluid for a medical application, said method comprising:

providing a piece of flexible tubing having smooth interior walls, the tubing comprising a single piece and having no adhesives on the interior surfaces;

providing a support device for the flexible tubing, the support device being configured to prevent flow constricting areas from forming in the flexible tubing; and

transporting a fluid through the flexible tubing.

38. (Currently Amended) A kink-resistant tubing apparatus comprising, in combination, a support structure and a weight bearing flexible intravenous tube, said support structure being configured to substantially prevent kinking in the weight bearing flexible intravenous tube disposed within said support structure.

39. (Currently Amended) A kink-resistant tubing apparatus comprising, in combination a support structure and a weight bearing flexible intravenous tube, said support structure being configured to substantially prevent kinking in the weight bearing flexible intravenous tube when disposed within said support structure, and said support structure being configured so that said flexible tubing is adjustable within said support structure.

40. (Currently Amended) A kink-resistant tubing apparatus comprising, in combination, a support structure and a flexible intravenous tube, said support structure being configured to be weight bearing to substantially prevent kinking in the flexible intravenous tube disposed within said support structure when weight is applied to said flexible tube.

41. (Currently Amended) A kink-resistant tubing apparatus comprising, in combination, a support structure and a flexible intravenous tube, said support structure being configured to substantially prevent kinking in the flexible intravenous tube disposed within said support structure when weight is applied to the flexible tube, and said support structure being configured so that the flexible tube is adjustable within said support structure.

42-43. (Canceled)

44-48. (Cancelled)

49. (Currently Amended) A kink resistant tubing apparatus comprising a support member, said support member comprising:

a solid rectangular block;

at least two channels through said ~~support member~~ solid rectangular block for retaining tubing; and

structure to support the weight of said tubing apparatus without substantially deforming tubing retained by said support member.

50. (Previously Presented) The kink resistant tubing apparatus according to claim 49, wherein said at least two channels are substantially parallel to each other.

51. (Cancelled).

52. (Currently Amended) The kink resistant tubing apparatus according to claim ~~51~~ 50, wherein said structure to support the weight of said tubing apparatus comprises a hole through said support member perpendicular to the said at least two channels.

53. (Cancelled)

54. (Currently Amended) ~~The kink resistant tubing apparatus according to claim 50, An~~ improved tubing device comprising a flexible support member, wherein said flexible support member comprises a curved portion between said at least two channels has at least one, and preferably a pair of channels, formed proximate the ends of the flexible support member.

55. (Currently Amended) The kink resistant tubing apparatus according to claim 54, wherein said structure to support the weight of said tubing apparatus comprises ~~said~~ a curved portion of said flexible support member between said at least two channels.

56. (Previously Presented) The kink resistant tubing apparatus according to claim 49, wherein said support member is configured to prevent deformation of tubing held by said support member upon the weight of said tubing apparatus being supported by said support member.

57. (Currently Amended) The kink resistant tubing apparatus according to claim 49, wherein said support member is ~~flexible~~ semi-rigid.

58. (Previously Presented) The kink resistant tubing apparatus according to claim 49, wherein said support member is substantially rigid.